

**ZUMA**  
®

## Li-ion Battery

**25.6V 50Ah**

LFP Li-ion Battery





**25.6V50Ah**

### Specification

| Model                            | ZUMA 25.6V50Ah  |
|----------------------------------|---|
| Nominal Voltage [V]              | 25.6  |
| Nominal Capacity [Ah]            | 50  |
| Total Energy [Wh]                | 1280  |
| Max. Charging Current [A]        | 50  |
| Recommended Charging Current [A] | 25  |
| Charging Voltage [V]             | 29.2  |
| Max. Discharging Current [A]     | 50  |
| End of Discharge Voltage [V]     | 22.4  |
| Pulse Discharge Current          | 100A @ 10s  |
| Dimension [W*D*H, mm]            | 330*172*214   |
| Weight [Kg]                      | 15.0  |
| Operation Humidity               | 0~95% RH (No condensing)  |
| Operating Temperature Range      | Charge: 0 ~ +50 °C;<br>Discharge: -20 ~ +55 °C                  |
| BMS Protection                   | Over charge, Over discharge,<br>Over temperature, Short circuit |
| Parallel Support                 | Yes, Max 2 Sets   |
| Series Support                   | No Support  |
| Cycle Life                       | >3000   |
| Designed Calendar Life           | >10 Years   |
| Certification                    | UN38.3, CE, MSDS  |



### Dimension:



Unit: mm

### SAFETY

- + Prismatic LiFePO<sub>4</sub> cells (50Ah), High consistency, long cycle life and much more safety.
- + UN38.3, CE certification for system.
- + The cycle life over 3000 times @80%DOD

### DESIGN

- + ABS container, replace VRLA battery perfectly.
- + Fast charge performance.
- + -20~+55 °C widely temperature range.
- + Maintenance free.
- + Integrated hardware BMS inside.
- + Independent protection for charge and discharge.
- + Over voltage, low voltage, over temperature and short circuit protection.

### BATTERY MANAGEMENT SYSTEM (BMS)

- Note:  
1. 80% DOD and to 80% of initial capacity.

The datasheet is subject to change without prior notification

Version 1.0